

Reptail LM - MM - SM comparison

Function	Reptail LM	Reptail MM	Reptail SM
Weight	7500 kg	5500 kg	3600 kg
Working thickness	0-400 mm	0 - 400 mm (option 150 - 550 mm)	0 - 300 mm (option 150 - 450 mm)
Working width	4,0 - 5,6 m	3,3 - 4,9 m	2,74 - 4,36 m
Working width	Option 4,0 - 6,2 m	Option 3,3 - 5,5 m	-
Working width	Option 3,5 m	Option 2,8 m	-
Telescope frame	Including in price. Open 40 cm	Including in price. Open 0- 40 cm	No
Compacting wheels	Including in price	Including in price	No
Transport dimensions	4290*1700*2980* mm	3490*1400*2980 mm	3300*2300*1300 mm
Warranty	12 months	12 months	12 months
Hydraulic valve	Hawe proportional	Hawe proportional	Hawe on/ off
Readiness for machine control	Including in price	Including in price	Option
Tilt automation	Including in price	Including in price	Including in price
Hydraulic filter	Including in price	Including in price	Including in price
Controlling	Joystick	Joystick	Display buttons
Display	4,3"	4,3"	4,3"
Slope sensor	Including in price	Including in price	Including in price
Thickness sensor	Including in price	Including in price	Including in price
Width sensor	Including in price	Including in price	Option
Customers colouring	Including in price	Including in price	Including in price
Reversible blades (middle edge)	Including in price	Including in price	Including in price
Double wheels for soft surfaces	Option	Option	Option
Spreader for geotextiles	Option	Option	Option
Laser automat for levelling	Option	Option	Option
Ultrasound automat for levelling	Option	Option	No
Recommended machine to work with	dozer, wheel loader	dozer, wheel loader	dozer, wheel loader, tractor, backhoe loader
Recommended machine size minimum	25 tons	16 tons	10 tons