



10


 \bigotimes

 \bigotimes

 \mathbb{O}

GEISM

 \bigotimes









Your benefits

- Easy and fast operation for all sleeper drilling applications
- Drilling precision is ensured by using the drill bushing
- Operational safety for on track use:
 - · Adjustable drilling depth limitation to avoid contacting with the ballast under the sleeper
 - Protective sheath on all the length
 - Auger brake in case the drill jam into the sleeper
 - Self-unlocking auger holding chuck to quickly clear the track



Specifications	
Engine	2 stroke - STIHL BT131
Engine power	1.4 kW (1.9 hp) 8,500 rpm
Mass (in working order)	Approx. 33 lbs. (14.9 kg)
Dimensions (without auger brake) (L x W x H)	21 x 15 x 35 in. (530 x 390 x 900 mm)
Maximum drilling depth	7.8 in. (200 mm)
Tool rotation speed	588 rpm
Maximal auger diameter	0.98 in. (25 mm)
Auger holding chuck diameter	0.63 in. (16 mm)

Consumables

• Drill bits (different diameters available)

Accessories

- Transport cases
- Drill brushing (different diameters available)
- Weight compensation trolley (different gauges available)

Optional equipments

- Gear box for hard wood sleeper
- $^{\circ}$ Auger holding chuck for cylindrical, graffenstaden or FS8489 drill bits

