



MODERN TRACK MACHINERY

Over 80 years of experience and innovation

PSD-3B

Portable Spike Driver

- Self-contained, one man operated, on-track spike driver with single articulated hydraulic actuated hammerhead.
- Able to drive spikes in hard wood ties in 5 to 6 seconds and faster in softwood ties.
- Mounted on four-wheel transverse trolley that permits working over both rails.
- Off-trackable by two persons.
- Two telescopic sheaths and a pneumatic system raising the machine at the end of drilling operation, so that it can be used without effort by operator.



Specifications:

Hydraulic Power Unit

- Flow - 8 GPM

Pressure - 2200 PSI

Pump - Gear type, direct drive through flex coupling

Oil: Shell Tellus T32, Oil level sight glass, 10 Micron return filter, return filter gauge

Cooling - air blast oil cooler

Controls - oil flow on/off valve

- Engine: Honda GX 390 air-cooled, 4 stroke gasoline, 13 HP, pull start with 6.5 litres (1.7 US gallons) fuel tank

Hammer: 1300 blows/minute

Size - 95"L x 34"W x 45"H (241 x 86 x 114 cm)

Weight: 585 lbs (266 kg)

www.geismar.com

We reserve the right to modify any equipment specification of the present offer to take into account the latest technical improvements and working conditions at the date of manufacturing. Illustrations may include optional equipment.



Customer Service: 1-800-563-1772 / sales@mtmgeismar.com



Customer Service: 847-697-7510 / info@geismar-mtm.com