


TURNOUT & TRACK LAYING SYSTEM

PEM-LEM

*Modular and efficient
track laying technology*



The most used method worldwide for track laying

Flexible installation

Safe remote-controlled solution



TURNOUT & TRACK LAYING SYSTEM

PEM-LEM

Your benefits

- Ease work preparation for diverse environment of situations (tunnels, bridges)
- Efficient organization by slewing tracks & turnouts or by transporting them on motorized transportation trolleys
- Enables the minimization of on-track time, increasing track availability
- Modular configuration for any track & turnout lengths and types
- Strong reduction of on-site staff

Specifications

Number of sets (PEM + LEM)	From 2 to 16	Lifting capacity	PEM	20 t
			LEM	20 t
Mass track panel or turnout	Up to 240 t	Lifting stroke	PEM	2,950 mm (116 in.)
			LEM	350 mm (14 in.)
Track / turnout length	From 6 to 160 m From 20 to 525 ft	Slewing stroke	PEM	1,375 mm (54 in.)
			LEM	± 400 mm (15,7 in.)
Displacement speed	6 km/h (3,7 mph)	Maximum feet opening	4,973 mm (196 in.)	
Ergonomics	Remote-controlled			

Composition of sets

- Gantries for lifting track and turnouts (PEM)
- Trolleys to transport track and turnouts (LEM)
- Temporary track with ramp (VPR)



PEM



LEM



Remote control



Longitudinal laying with temporary track (VPR)



TURNOUT & TRACK LAYING SYSTEM


PEM-LEM

Track laying methodology


1. Lifting of tracks & turnouts by gantries and positioning of lorries under the load




2. Transporting to laying area and preparation to use the ramp




3. Tracks & turnouts on place and lifting the load with gantries



4. Lorries evacuation and lay down the load on area



5. Adjusting the tracks & turnouts (lateral and longitudinal slewing)



6. Evacuation of gantries and lorries




TURNOUT & TRACK LAYING SYSTEM

PEM-LEM

Modularity of the solution with one operator and one remote control

- Maximum laying length: 160 m (525 ft)



- Minimum laying length: 6 m (20 ft)



Work site typical efficiency

- Laying 160 m (525 ft) turnout in approximately 2 hours (implementation and evacuation of machines)

Other applications

- Transport of concrete mixers
- Transport of tippers
- Transport of poles
- Transport of metallic bridges

